







Product card

Roof sandwich panel







Technical information



Board cross-section



Joining of panels




Technical information

Core	PIR						
Density [kg/m³]	40 ± 3						
PIR panel thickness [mm]	40	60	80	100	120	160	
Weight [kg/m²]	9,8	10,6	11,5	12,3	13,2	14,8	
Effective width [mm]	1050						
Total width [mm]	1127						
Min. panel length [mb]	2,5						
Max. panel length [mb]	13,5						
Outer/inner sheet thickness [mm]	0,4-0,7 / 0,4-0,7						
U-factor [W/m²K].	0,55	0,37	0,28	0,22	0,18	0,14	
Reaction to fire	B-s1,d0						
Wall resistance to external fire	REI15	REI20	REI30	REI45	REI45	REI45	
Type of profiling ext. / int.	[T40] / [M], [T] , [F]						
Corrosion resistance ext. / ext.	C1, C2, C3 (C4 ÷ C5) / A1 (A2 ÷ A5)						
Standard coatings	Poliester Interior [INT], Poliester Standard [RAL], HERCULIT [HC], MULTILAYER 40 [MLT]						
Special coatings	PVDF, PUR, PVC (P), PVC (F) - FoodSafe						
Accessories	Fastening system, gaskets, flashings, lighting profiles						

Packaging of sandwich panels

Panel thickness [mm]	Modular width [mm]	Quantity of panels in a package	Quantity of packages per vehicle	Package height [mm]	Package weight [kg]	Maximum loading length [m]	Quantity of panels per vehicle [m2]
40	1050	12	6	2430	1587,6	13,5	1020,6
60	1050	10	6	2700	1444,5	13,5	850,5
80	1050	10	4	2570	1552,5	13,5	567
100	1050	8	4	2420	1339,2	13,5	453,6
120	1050	7	4	2420	1247,4	13,5	396,9
160	1050	6	4	2600	1206,9	13,5	340,2

External profiling




TRAPEZOIDAL 40 [T40]




Internal profiling



TRAPEZOIDAL[T]









FLAT [F]

Coatings and colors

POLIESTER Interior [INT] - Available colors for interior cladding



POLIESTER Standard [RAL] - Available colors for exterior cladding



HERCULIT [HC]



MULTILAYER 40 [MLT] - Available colors for exterior cladding





Printing technology does not allow faithful rendering of colors. Therefore the colors shown are indicative and may differ from actual colors.




In addition, on individual order, non-standard colors and coatings are available, outside the palette shown (PVDF, PUR, PVC (P), PVC (F) - FoodSafe).

Coating parameters

Code	Coating thickness	Corrosion resistance	UV resistance	
POLIESTER Interior [INT]	15 μm	RA2	Not applicable	
POLIESTER Standard [RAL]	25 μm	RC3	RUV2	
HERCULIT [HC]	35 μm	RC4	RUV4	
MULTILAYER 40 [MLT]	40 µm	RC3	RUV3	

Notes







MODULAR SERIES



COMPACT SERIES



CLASSIC SERIES



RETRO SERIES



PANEL SERIES







TRAPEZOIDAL











Wall Sandwich PANELS



SKRIN, LINEA, SINUS









PERFORATION







